

Capa	Caparol Samtex 20 ELF baza 1						
Versio 1.0	n Revision Date: 19.12.2022	SDS N 602007	lumber: 76	Date of last issue: - Date of first issue: 19.12.2022			
SECT	ION 1: Identification of	the sub	ostance/mixt	ure and of the company/undertaking			
1.1 Pro	oduct identifier						
Ti	ade name	: Ca	parol Samtex :	20 ELF baza 1			
1.2 Re	levant identified uses of t	he subs	tance or mixt	ure and uses advised against			
-	se of the Sub- ance/Mixture	: Wa	iter-borne coa	tings			
Recommended restrictions : within adequate application - none on use			application - none				
1.3 De	tails of the supplier of the	safety (data sheet				
	ompany	: DA Mie	W Baltica SIA era iela 30C				
Т	elephone		69 Salaspils, \$ 7167500072	Salaspils nov.			
	-mail address Responsi- e/issuing person	: info	o@daw.lv				
	anufacturer:						
C	ompany		3dörfer Straße				
	64372 Ober-Ramstadt Telephone : +496154710 Telefax : +49615471222			σιανι			
1.4 En	nergency telephone						
Er	nergency telephone 1			sības un glābšanas dienests: 112 ijas centrs,Saindēšanās un zāļu informācijas			

Valsts ugunsdzesības un glabsanās dienests. 112 Valsts Toksikoloģijas centrs,Saindēšanās un zāļu informācijas centrs, Hipokrāta 2, Rīga, Latvija, LV-1079; strādā 24 h diennaktī. Tālr. 67042473



Caparol Samtex 20 ELF baza 1

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	19.12.2022	6020076	Date of first issue: 19.12.2022

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Precautionary Statements		P101 If medical advice is needed, have product container or
	·	label at hand.
		P102 Keep out of reach of children.

Additional Labeling

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2Hisothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Caparol Samtex 20 ELF baza 1

VersionRevision Date:SDS Number:Date of last issue: -1.019.12.20226020076Date of first issue: 19.12.2022	
--	--

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Emulsion paint, emission-free and solvent-free

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
titanium dioxide; [in powder form containing 1 % or more of parti- cles with aerodynamic diameter ≤ 10 µm]	13463-67-7 236-675-5 022-006-00-2 01-2119489379-17	Carc. 2; H351	>= 10 - < 20
propylidynetrimethanol	77-99-6 201-074-9 01-2119486799-10	Repr. 2; H361fd	>= 0,1 - < 1
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 Acute Tox. 2; H330 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1 specific concentration limit Skin Sens. 1; H317 >= 0,05 %	>= 0,025 - < 0,05
reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2- methyl-2H-isothiazol-3-one (3:1)	55965-84-9 613-167-00-5 01-2120764691-48	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317	>= 0,0002 - < 0,0015

Caparol Samtex 20 ELF baza 1



LV / EN

rsion	Revision Date: 19.12.2022	SDS Number: 6020076	Date of last issue: - Date of first issue: 19.12.2022
			Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100 specific concentration limit Skin Corr. 1C; H314 >= 0,6 % Skin Irrit. 2; H315 0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 >= 0,0015 %
Subst kaolin	ances with a workpla	ce exposure limit : 1332-58-7	Eye Dam. 1; H318 >= 0,6 %
Kaolin		310-194-1	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice	:	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Move out of dangerous area. First aider needs to protect himself.
If inhaled	:	Move to fresh air.
In case of skin contact	:	Do NOT use solvents or thinners. In case of contact, immediately flush skin with soap and plenty of water.



Caparol Samtex 20 ELF baza 1

Version 1.0	Revision Date: 19.12.2022	SDS Number: 6020076	Date of last issue: - Date of first issue: 19.12.2022	
In cas	e of eye contact	IF IN EYES: Rins	ersists: Get medical advice/ attention. se cautiously with water for several minutes. lenses, if present and easy to do. Continue	
If swallowed		Clean mouth with	Seek medical advice. Clean mouth with water and drink afterwards plenty of water. If swallowed, DO NOT induce vomiting.	

4.2 Most important symptoms and effects, both acute and delayed None known.

4.3 Indication of any immediate medical attention and special treatment needed Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	Use water spray, alcohol-resistant foam, dry chemical or car- bon dioxide. Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment. Do not use a solid water stream as it may scatter and spread fire.
Unsuitable extinguishing media	:	None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire	:	In case of fire hazardous decomposition products may be
fighting		produced such as:
		Carbon monoxide, carbon dioxide and unburned hydrocar-
		bons (smoke).

5.3 Advice for firefighters

Special protective equipment for fire-fighters	:	Wear self-contained breathing apparatus for firefighting if nec- essary.
Further information	:	Standard procedure for chemical fires. The product itself does not burn.



Caparol Samtex 20 ELF baza 1

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	19.12.2022	6020076	Date of first issue: 19.12.2022

SECTION 6: Accidental release measures

6.1 Personal precautions, protecti	ve equipment and emergency procedures
Personal precautions	Use protective shoes or boots with rough rubber sole. Material can create slippery conditions. Do not get in eyes, on skin, or on clothing.
6.2 Environmental precautions	
Environmental precautions	 Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. Do not flush into surface water or sanitary sewer system.
6.3 Methods and material for conta	ainment and cleaning up
Mathada far alaaning un	Kaap in quitable, closed containers for dispessel

Methods for cleaning up	:	Keep in suitable, closed containers for disposal.
		Soak up with inert absorbent material (e.g. sand, silica gel,
		acid binder, universal binder, sawdust).

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling	
Advice on safe handling :	For personal protection see section 8. No special technical protective measures required. In addition, the current technical information for this product and its application on www.caparol.com must be observed.
Hygiene measures :	Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminat- ed clothing and protective equipment before entering eating areas.
7.2 Conditions for safe storage, inc	cluding any incompatibilities
Requirements for storage : areas and containers	Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight. Store at room temperature in the original container. Containers which are opened must be care- fully resealed and kept upright to prevent leakage.
Advice on common storage :	Keep away from oxidizing agents and strongly acid or alkaline materials.
7.3 Specific end use(s)	
Specific use(s) :	This information is not available.



Caparol Samtex 20 ELF baza 1

VersionRevision Date:SDS Number:Date of last issue: -1.019.12.20226020076Date of first issue: 19.12.2022	
--	--

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
titanium dioxide; [in powder form con- taining 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	AER 8 st	10 mg/m3	LV OEL
kaolin	1332-58-7	TWA (Respirable dust)	0,1 mg/m3	2004/37/EC
	Further information: Carcinogens or mutagens			
		AER 8 st (inhal- able fraction)	0,1 mg/m3 (Silica)	LV OEL

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of expo- sure	Potential health ef- fects	Value
titanium dioxide; [in powder form contain- ing 1 % or more of particles with aerody- namic diameter ≤ 10 µm]	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3
propylidynetrimetha- nol	Consumers	Skin contact	Acute systemic ef- fects	83,30 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	1,68 mg/kg bw/day
	Consumers	Inhalation	Acute systemic ef- fects	925,00 mg/m3
	Consumers	Ingestion	Acute systemic ef- fects	50,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	5,03 mg/m3
	Consumers	Skin contact	Long-term systemic effects	1,68 mg/kg bw/day
	Workers	Inhalation	Acute systemic ef- fects	3037,30 mg/m3
	Workers	Inhalation	Long-term systemic effects	19,54 mg/m3



Caparol Samtex 20 ELF baza 1

Version 1.0	Revision Date: 19.12.2022	SDS Numb 6020076			last issue: - first issue: 19.12.2022	
	V	Vorkers	Skin conta	ct	Acute systemic ef- fects	138,80 mg/kg bw/day
	V	Vorkers	Skin conta	ct	Long-term systemic effects	2,79 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
titanium dioxide; [in powder form containing 1 % or more of parti- cles with aerodynamic diameter ≤ 10 µm]	Sewage treatment plant	100 mg/l
	Fresh water	0,184 mg/l
	Soil	100 mg/kg dry weight (d.w.)
	Sea water	0,0184 mg/l
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sea sediment	100 mg/kg dry weight (d.w.)
	Intermittent use/release	0,193 mg/l
propylidynetrimethanol	Fresh water	1 mg/l
	Sewage treatment plant	100 mg/l
	Sea sediment	0,351 mg/kg dry weight (d.w.)
	Sea water	0,1 mg/l
	Soil	0,241 mg/kg dry weight (d.w.)
	Fresh water sediment	3,505 mg/kg dry weight (d.w.)
	Intermittent use/release	10 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection Hand protection	:	Goggles
Material	:	Nitrile rubber
Glove thickness	:	0,2 mm
Protective index	:	Class 3
Remarks	:	Before removing gloves clean them with soap and water. Wear suitable gloves tested to EN374.
Skin and body protection	:	Safety shoes Long sleeved clothing Choose body protection according to the amount and con- centration of the dangerous substance at the work place. Skin should be washed after contact.



Caparol Samtex 20 ELF baza 1

Version	Revision Date: 19.12.2022	SDS Number:	Date of last issue: -
1.0		6020076	Date of first issue: 19.12.2022
Resp	iratory protection	quired. During spray a	spiratory protective equipment normally re- pplication: Do not breathe spray dust. Use ation filter for paint spraying.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Color Odor Melting point/freezing point	:	liquid No data available No data available
Boiling point/boiling range	:	ca. 100 °C
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	not determined
Flash point	:	Not applicable
Autoignition temperature	:	not determined
Decomposition temperature	:	Not applicable
рН	:	8 - 9 Concentration: 100 %
Viscosity Viscosity, dynamic	:	No data available
Solubility(ies) Water solubility	:	completely miscible
Partition coefficient: n- octanol/water	:	Not applicable
Vapor pressure	:	ca. 23,4 hPa (20 °C)
Relative density	:	not determined
Density	:	1,3800 g/cm3
Relative vapor density	:	Not applicable
9.2 Other information Explosives	:	Not applicable



Сар	arol Samtex 20 ELI	F baza 1
Versio 1.0	on Revision Date: 19.12.2022	SDS Number:Date of last issue: -6020076Date of first issue: 19.12.2022
C	Dxidizing properties	: Not applicable
F	Flammability (liquids)	: The product is not flammable.
SEC	ΓΙΟΝ 10: Stability and re	activity
	Reactivity	ad applied as directed
	No decomposition if stored ar	וע מאטוובת אז מוופטובת.
	Chemical stability No decomposition if stored ar	nd applied as directed.
10.3 F	Possibility of hazardous rea	actions
ŀ	lazardous reactions	: No decomposition if stored and applied as directed.
10.4 (Conditions to avoid	
C	Conditions to avoid	: Protect from frost, heat and sunlight.
10.5 I	ncompatible materials	
Ν	Aaterials to avoid	: Incompatible with acids and bases. Incompatible with oxidizing agents.
10.6 H	Hazardous decomposition	products
Ν	No decomposition if stored ar	nd applied as directed.
SEC	FION 11: Toxicological ir	nformation
11.1 I	nformation on hazard clas	ses as defined in Regulation (EC) No 1272/2008
ļ	Acute toxicity	

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity	:	LD50 (Rat): 532 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 0,4 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 (Rat): > 2.000 mg/kg



Caparol Samtex 20 ELF baza 1

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	19.12.2022	6020076	Date of first issue: 19.12.2022

(3:1):					
Acute oral toxicity	: LD50 (Rat): 66 mg/kg Method: OECD Test Guideline 401				
Acute inhalation toxicity	: LC50 (Rat): 0,17 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403				
Acute dermal toxicity	: LD50 (Rat): > 141 mg/kg Method: OECD Test Guideline 402				
Skin corrosion/irritation					
Not classified based on ava	ilable information.				
Serious eye damage/eye i					
Not classified based on ava	ilable information.				
Respiratory or skin sensit	ization				
Skin sensitization					
Not classified based on ava	ilable information.				
Respiratory sensitization					
Not classified based on ava	ilable information.				
Germ cell mutagenicity					
Not classified based on ava	liable information.				
Carcinogenicity Not classified based on ava	ilable information				
Reproductive toxicity					
Not classified based on ava	ilable information.				
STOT-single exposure					
Not classified based on ava	ilable information.				
STOT-repeated exposure					
Not classified based on ava	ilable information.				
Aspiration toxicity					
Not classified based on ava	ilable information.				
Information on other haza	ırds				
Endocrine disrupting prop	perties				
Product:					
Assessment	: The substance/mixture does not contain components consid-				

ered to have endocrine disrupting properties according to



Version 1.0	Revision Date: 19.12.2022		0S Number: 20076	Date of last issue: - Date of first issue: 19.12.2022	
				e 57(f) or Commission Delegated regulation 00 or Commission Regulation (EU) 2018/605 at or higher.	
SECTION	N 12: Ecological info	orma	tion		
12.1 Toxi	city				
Com	ponents:				
	enzisothiazol-3(2H)-oi ity to fish	ne: :	Exposure time	ynchus mykiss (rainbow trout)): 2,2 mg/l e: 96 h D Test Guideline 203	
	ity to daphnia and othe tic invertebrates	er : EC50 (Daphnia): 3,27 mg/l Exposure time: 48 h Method: OECD Test Guideline 202			
Toxic plants	ity to algae/aquatic s	to algae/aquatic : EC50 (Selenastrum capricornu Exposure time: 72 h Method: OECD Test Guideline			
M-Fa icity)	ctor (Acute aquatic tox-	:	1		
	M-Factor (Chronic aquatic : toxicity)		1		
react (3:1):		2-me	ethyl-2H-isothia	azol-3-one and 2-methyl-2H-isothiazol-3-one	
. ,	ctor (Acute aquatic tox-	:	100		
M-Fa toxici	ctor (Chronic aquatic ty)	:	100		
	istence and degradab ata available	ility			
I2.3 Bioa	ccumulative potential				
Com	ponents:				
(3:1):		2-me	ethyl-2H-isothia	azol-3-one and 2-methyl-2H-isothiazol-3-one	
	ion coefficient: n- ol/water	:	log Pow: <= 0 Method: OEC	,71 D Test Guideline 117	



Caparo	ol Samtex 20 EL	_F b	aza 1			
Version 1.0	Revision Date: 19.12.2022		DS Number: 20076	Date of last issue: - Date of first issue: 19.12.2022		
	i lity in soil ata available					
12.5 Resu	Its of PBT and vPvB	asse	ssment			
Prod	uct:					
	ssment	:	: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels 0.1% or higher.			
12.6 Endo	ocrine disrupting pro	pertie	s			
Prod	<u>uct:</u>					
Asse	ssment	:	 The substance/mixture does not contain components co ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/6 levels of 0.1% or higher. 			
12.7 Othe	r adverse effects					
Product: Additional ecological infor- mation		:	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.			
SECTION	N 13: Disposal cons	sider	ations			
13.1 Wast	te treatment methods	;				
Produ	uct	:	safe way in ac	all related packaging must be disposed of in a cordance with the full requirements of the local, nal and international authorities.		
			Waste should i	not be disposed of via wastewater.		
Conta	aminated packaging	:	Only completely emptied containers should be given for recy- cling.			
Wast	e Code	:	: used product 080112, waste paint and varnish other than those mentioned			

SECTION 14: Transport information

П	14.1	UN	number	or ID	number
---	------	----	--------	-------	--------

in 08 01 11*



Caparol Samtex 20 ELF baza 1						
	ersion .0	Revision Date: 19.12.2022		DS Number: 20076	Date of last issue: - Date of first issue: 19.12.2022	
	ADR		:	Not regulated as a	a dangerous good	
	RID		:	Not regulated as a	a dangerous good	
	IMDG		:	Not regulated as a	a dangerous good	
	ΙΑΤΑ		:	Not regulated as a	a dangerous good	
14	4.2 UN pro	oper shipping name				
	ADR		:	Not regulated as a	a dangerous good	
	RID		:	Not regulated as a	a dangerous good	
	IMDG		:	Not regulated as a	a dangerous good	
	ΙΑΤΑ		:	Not regulated as a	a dangerous good	
14	4.3 Transp	port hazard class(es)				
	ADR		:	Not regulated as a	a dangerous good	
	RID		:	Not regulated as a		
	IMDG		:	Not regulated as a	0 0	
	ΙΑΤΑ		:	Not regulated as a		
14	4.4 Packir	ng group		0		
	ADR			Not regulated as a	a dangerous good	
	RID			Not regulated as a		
	IMDG		:	Not regulated as a		
	IATA (Cargo)	:	Not regulated as a		
	-	Passenger)	:	Not regulated as a		
114	•	onmental hazards	•	Not regulated as a		
11 ''		gulated as a dangerous	s ao	od		
14		al precautions for use	Ũ			
	Remar	•	:	Not classified as o lations.	langerous in the meaning of transport regu-	
14	14.7 Maritime transport in bulk according to IMO instruments					
Not applicable for product as supplied.						

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on : Not applicable the market and use of certain dangerous substances,



LV / EN

ersion)	Revision Date: 19.12.2022	SDS Number: 6020076	Date of last issue: - Date of first issue: 19.12.2022
REAC	res and articles (Anne CH - Candidate List of ern for Authorization (Substances of Very Hi	igh : This product is a mixture and doe not contain Substances of Very H Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemi safety assessment has to be ger ated.
plete Regul tants REAC	the ozone layer ation (EU) 2019/1021 (recast)	009 on substances tha on persistent organic s subject to authorisation	pollu- : Not applicable
pean contro	so III: Directive 2012/1 Parliament and of the of major-accident ha prous substances.	Council on the	Not applicable
Volati	le organic compounds	s : Directive 2004/ < 0.1 % < 1 g/l	42/EC

Cabinet Regulation No.325 of 15 May 2007 (as amended) "Labour Protection Requirements when Coming in Contact with Chemical Substances at Workplaces". Cabinet of Ministers, Regulation No. 113 (18.02.2021) on "Procedures for accounting of waste and its shipments" Cabinet Regulation No.795 of 22 December 2015 on Procedures for Registration of Chemical Substances and Mixtures and Their Database.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: Other information

Full text of H-Statements

H301	:	Toxic if swallowed.
H302	:	Harmful if swallowed.
H310	:	Fatal in contact with skin.
H314	:	Causes severe skin burns and eye damage.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H330	:	Fatal if inhaled.
H351	:	Suspected of causing cancer if inhaled.



Caparol Samtex 20 ELF baza 1

Versio 1.0	n Revision Date: 19.12.2022		9S Number: 20076	Date of last issue: - Date of first issue: 19.12.2022
H H H	361fd 400 410 411	:	 Suspected of damaging fertility. Suspected of damaging fertility. Suspected of damaging unborn child. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects. 	
_	UH071 ull text of other abbrevia	: ations	Corrosive to the r	espiratory tract.
A A C E R S S S	cute Tox. quatic Acute quatic Chronic arc. ye Dam. epr. kin Corr. kin Irrit. kin Sens. 004/37/EC		Acute toxicity Short-term (acute) aquatic hazard Long-term (chronic) aquatic hazard Carcinogenicity Serious eye damage Reproductive toxicity Skin corrosion Skin irritation Skin sensitization Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutage	
- 20	V OEL 004/37/EC / TWA V OEL / AER 8 st		at work Latvia. Occupational exposure limit values Long term exposure limit Limit value measured and calculated for an 8-hour period	

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AlIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Coil Aviation Organization; IESC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Convention for the Prevention of 50% of a test population; LD50 - Lethal Dose to 50% of a test population; ICAO - International Convention for the Prevention of Pollution from Observable Effect Loading Rate; NZIGC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation,

Further information

Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite



Caparol Samtex 20 ELF baza 1

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	19.12.2022	6020076	Date of first issue: 19.12.2022

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

LV / EN