

SketchPaint Transparent – Technical Data Sheet



Producer: MagPaint Europe BV, Riezenweg 2, NL-7071 PR Uft, www.magpaint.com
Distributor: SIA "Krāsu serviss", Vienības gatve 93, Rīga, Latvija LV-1058,
Tel.:+ 371 669 39 669, info@krasas.lv, www.krasas.lv

1. Description:

SketchPaint Transparent is a two-component water-based coating for indoor application. SketchPaint Transparent is based on an acrylate binder with an isocyanate hardener and additives. SketchPaint Transparent is available in a glossy or matt version. A piece of a wall that has been treated with SketchPaint Transparent can be written on with whiteboard markers and easily cleaned. Tip: SketchPaint Gloss is easier to clean than SketchPaint Matt. One layer is usually sufficient for a good result. You can use our SketchMarkers, SketchCleaner or complete SketchKit to write on and clean the surface. For a magnetic whiteboard, the desired surface can first be treated with MagnetPaint. MagnetPaint can be overcoated with SketchPaint Transparent or first be changed to the desired colour.

Contains little to no solvent.

2. Application:

SketchPaint Transparent can be applied indoors on any non-absorbent surface. Walls, doors, kitchen cabinets, furniture, etc. As long as there is a good pre-treatment of the substrate. SketchPaint Transparent creates a whiteboard surface in play areas, living rooms, kitchens, bedrooms, office spaces; basically, anywhere you want to write or draw something. The transparent product allows you to create a whiteboard in any colour, with any desired effect or pattern. You can put notes, drawings, recipes, shopping lists, task lists, schedules, calendars, and anything else you can think of on a whiteboard integrated into the interior. Combining this with our MagnetPaint creates even more possibilities. Let your creativity run free, or increase your productivity.

3. Equipment:

SketchPaint Transparent can be applied with a short-haired finish roller.
Clean used tools with water.

4. Theoretical consumption:

8 m²/L for one layer, depending on many factors such as porosity and roughness of the substrate and material loss during application.

SketchPaint Transparent – Technical Data Sheet



Producer: MagPaint Europe BV, Riezenweg 2, NL-7071 PR Ulft, www.magpaint.com
Distributor: SIA "Krāsu serviss", Vienības gatve 93, Rīga, Latvija LV-1058,
Tel.: +371 669 39 669, info@krasas.lv, www.krasas.lv

5. Instructions for use – Application:

Pre-treatment: It is best to properly clean and sand the substrate. SketchPaint can be applied directly on slightly absorbent surfaces such as wood, MDF, plasterboard and MagnetPaint. Pre-treat highly absorbent mineral and wood substrates with a suitable primer. Sand existing coatings or plastic surfaces for a good matt finish. Remove any damaged or peeling paint layers. If necessary, first apply the desired colour to the substrate with a suitable paint and let it dry well. Ensure a surface that is as smooth as possible. Any irregularities will be harder to clean.

Application: Do not process at a temperatures below + 10°C and/or a relative humidity of more than 80%. Wear protective gloves when applying SketchPaint. Remove the cans from each other, open the large base can (B) and stir well. Then open the small hardener can (A) and scrape the complete contents at the base into the large can. Stir the mixture thoroughly for 3 minutes. The base will be slightly thicker after adding the hardener. If necessary, the SketchPaint can be diluted with water. Apply SketchPaint within one hour after mixing. Pour the mixture into a roller box and saturate the roller. Remove excess paint from the roller and apply the SketchPaint to the surface with long vertical strokes. Always paint wet-on-wet to prevent premature drying. Distribute SketchPaint evenly as quickly as possible and stop rolling. SketchPaint is tack-free after about 4 hours. Remove masking tape within 1 hour after applying the SketchPaint to prevent damage to the edges. A second layer can be applied within 4 hours without problems. If the SketchPaint has hardened, it must first be sanded with ultra-fine sandpaper and then cleaned thoroughly.

Additional tips:

- Regularly check that the entire surface is covered.
- For large surfaces, it is wise to dilute the SketchPaint to prevent premature drying.
- If you use multiple cans for one surface, make sure that the next can is mixed and ready before the first can is empty.
- Use a fresh roller and roller box for each SketchPaint can to prevent contamination with old paint.
- Do not close cans containing mixed material.
- Try not to apply more or less paint than the consumption prescribes. Layers that are too thick become bumpy, while layers that are too thin may cause problems with erasing.
- Masking tape not removed in time? Cut along the masking tape with a utility knife before removing it.

SketchPaint Transparent – Technical Data Sheet



Producer: MagPaint Europe BV, Riezenweg 2, NL-7071 PR Uft, www.magpaint.com
Distributor: SIA "Krāsu serviss", Vienības gatve 93, Rīga, Latvija LV-1058,
Tel.:+ 371 669 39 669, info@krasas.lv, www.krasas.lv

6. Instructions for use – Use:

Let SketchPaint dry for 5 days before writing on it. SketchPaint can be written on with our SketchMarkers, available in sets of 4 pieces in Black, Blue, Green, Red or different colours. In addition, our SketchKit offers a complete starter set of 4 colour markers, a microfibre cloth and a bottle of SketchCleaner. Stubborn marker residues can be removed with a damp cloth or our SketchCleaner. Preferably use the SketchCleaner every day to keep the surface clean. Inadvertently used a waterproof pen? Carefully remove stubborn "ghosting" with acetone or thinner. Do not use abrasive cleaning agents. We recommend the use of our tried and tested SketchMarkers. With other brands, first test whether it can be erased before writing on the entire surface.

7. Storage advice:

In unopened packaging, in a dry, well-ventilated room, away from direct sunlight at temperatures between 5°C and 35°C. NOTE: do not close after mixing!

8. VOC/Certification:

EU limit value for this product (2004/42/EC, Cat. GWB, 2010): 140 g/L. This product contains 0 g/L

SketchPaint Transparent – Technical Data Sheet



Producer: MagPaint Europe BV, Riezenweg 2, NL-7071 PR Ulft, www.magpaint.com
Distributor: SIA "Krāsu serviss", Vienības gatve 93, Rīga, Latvija LV-1058,
Tel.: +371 669 39 669, info@krasas.lv, www.krasas.lv

9 Specifications:

Commodity code:	320910.
Colour:	Transparent.
Sheen:	Glossy or matt.
Density:	1.05 kg/L, mixed product.
Layer thickness:	Approx. 50 µm, one layer
Theoretical consumption:	Approx. 8-10 m ² /L, depending on the substrate and application method.
Viscosity:	Ready for use, dilute up to 10% with clear water if necessary.
VOC:	EU limit value for this product (2004/42/EC, Cat. GWB, 2010): 140 g/L. This product contains 0 g/L
Processing:	Temperature: > +10°C. Humidity: <80 RH
Tack-free:	Approx. 4 hours at 20°C and 65% RH
Additional layers:	Approx. 6 hours at 20°C and 65% RH
Ready to use:	Approx. 5 days at 20°C and 65% RH
Units:	0.5 litres - 1 litre.
Shelf life:	At least 18 months under the right storage conditions.

LITTLE TO NO SOLVENT
MEETS HEALTH AND SAFETY REQUIREMENTS FOR PROFESSIONAL INDOOR USE

SAFETY DATA SHEET AVAILABLE AT MAGPAINT EUROPE OR DOWNLOAD AT WWW.MAGPAINT.COM