

KOLOREX Priming Oil



Priming oil for exterior wooden surfaces

- Protects wood against water penetration
- Prevents blue stain and mould growth
- Creates a good adhesive surface

Product description:

Colorless, solvent-based priming oil/antiseptic for impregnating wood outdoors before further treatment with paint. Particularly suitable for impregnating board ends, joints, screws and nails. Contains tung wood oil and linseed oil, which provides deep penetration into the wood and protects against moisture absorption, cracking and rotting. Anti-mold additives effectively prevent blue stain and mold growth. Kolorex Priming Oil creates a good adhesive base for topcoat application.

Kolorex Priming Oil is produced in Sweden.



Swedish paint
Since 1955

| | |
|--------------------------------|---|
| Area of application | Outdoors |
| Binder | Alkyd/linseed oil/tung tree oil |
| Volume Solids | 15% |
| Weight Solids | 18% |
| Density | 0,82 g/cm ³ |
| Gloss | Dependent on surface |
| Thinner/Cleaning | White spirit/ Naphtha |
| Material consumption | 4-8 m ² /L |
| Temperature at painting | Air, surface and material temperature should be above +5°C and the relative humidity during application and drying should be below 80%. |
| Tools for painting | Brush |
| Dust dry | 1 h |
| Re-paintable | 6 h |
| Shelf life | 2 years if unopened, frost free storage |
| Colour | Clear |
| Flammability | 3 |
| VOC category | (Cat. A/h): 750 g/l (2010) |

KRASO

How to use

Surface preparation and application conditions

The surface must be clean and dry, with the moisture content in the wood 12-16%. Air, surface and material temperature should be above +5°C and the relative humidity during application and drying should be below 80%. In case of black mould or algae stains, treat the surface with an anti-mould disinfectant, rinse thoroughly with water, and allow it to dry completely.

Application

Stir the oil thoroughly in the can before use. Apply generously by brushing or dipping. The oil must be completely absorbed into the wood without leaving a film on the surface. Apply especially thoroughly to the ends of boards, joints, nail and screw placing points. Apply several times until the wood no longer absorbs the oil. Clean the areas where the oil has not soaked in and the twig points with a cloth soaked in white spirit. Do not apply in direct sunlight or on surfaces that are excessively heated. The solvent evaporates too quickly in the heat and reduces the penetration of the oil deep into the wood, which can cause poor adhesion of the subsequently applied paint.

N.B.! As rags soaked in oil can self-ignite, store them in water or dry them in the open air until disposal, or burn them immediately!

Storage

Store in dry and cool place in unopened original packaging. Shelf life is 2 years from the date of manufacture.

Environmental and labor protection, waste collection

Use personal protective equipment. Ensure good ventilation when sanding treated surfaces. Wipe off the tools thoroughly before cleaning with white spirit. Close the jar carefully after use and keep out of the reach of children. Liquid residues must not be drained into the sewer, but must be taken to a local collection point.

Protect the environment, like we do.

Danger May be fatal if swallowed and enters airways. Repeated exposure may cause skin dryness or cracking. Keep out of reach of children. Avoid release to the environment. Avoid breathing vapours/spray. IF SWALLOWED: Immediately call a POISON

The above information is based on our existing knowledge, laboratory tests, experience and information that the manufacturer has been able to provide at the time of preparing the product specification. The manufacturer's management system is certified and complies with the international standards ISO 9001 and ISO 14001. The manufacturer and the distributor have no control over the conditions of use or other factors that may affect the use and application of the product. The buyer/user is responsible for the suitability and use of the product. Please note that all of the above concerning the use of the product is dependent on the correct preparation of the surface and the surrounding environment.

CENTER/doctor. Do NOT induce vomiting. Dispose of contents/container in accordance with local regulations. Contains: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics. Contains a biocidal product for the preservation of dry-film: IPBC. May produce an allergic reaction. Contains Linseed oil. Risk of spontaneous combustion. Spills and used cloths are to be collected and deposited in a fireproof waste container, hung to dry outdoors or burned under supervision.

This product contains a maximum of 750 g VOC/L. The limit value is 750 g VOC/L (cat. A/h).